


CGH35015

15 W, 3.3-3.9 GHz, 28V, GaN HEMT for WiMAX

Description

The CGH35015 is a gallium nitride (GaN) high electron mobility transistor (HEMT) designed specifically for 802.16-2004 WiMAX Fixed Access applications. GaN HEMTs offer high efficiency, high gain and wide bandwidth capabilities, which makes the CGH35015 ideal for 3.3-3.9 GHz WiMAX and BWA amplifier applications. The transistor is available in both screw-down, flange and solder-down, pill packages.



Package Types: 440166 and 440196
PNs: CGH35015F and CGH35015P

Typical Performance Over 3.3-3.8 GHz ($T_c = 25^\circ\text{C}$) of Demonstration Amplifier

| Parameter | 3.3 GHz | 3.4 GHz | 3.5 GHz | 3.6 GHz | 3.7 GHz | 3.8 GHz | Units |
|--|---------|---------|---------|---------|---------|---------|-------|
| Small Signal Gain | 13.6 | 12.8 | 12.3 | 12.2 | 12.3 | 12.8 | dB |
| EVM at $P_{AVE} = 24$ dBm | 2.71 | 2.31 | 2.1 | 2.12 | 2.54 | 3.04 | % |
| EVM at $P_{AVE} = 33$ dBm | 2.63 | 2.29 | 1.93 | 1.70 | 1.70 | 2.14 | % |
| Drain Efficiency at $P_{AVE} = 33$ dBm | 24.0 | 25.5 | 26.1 | 25.6 | 23.8 | 2.38 | % |

Note:

Measured in the CGH35015F-AMP amplifier circuit, under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, 5ms Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3, PAR = 9.8 dB @ 0.01% Probability on CCDF.

Features

- 3.3 - 3.9 GHz Operation
- 15 W Peak Power Capability
- 12 dB Small Signal Gain
- 2.0 W P_{AVE} at < 2.0% EVM
- 26% Efficiency at 2 W Average Power
- WiMAX Fixed Access 802.16-2004 OFDM
- WiMAX Mobile Access 802.16e OFDMA

Large Signal Models Available for ADS and MWO



Absolute Maximum Ratings (not simultaneous) at 25°C Case Temperature

| Parameter | Symbol | Rating | Units | Conditions |
|---|-----------------|-----------|-------|------------|
| Drain-Source Voltage | V_{DSS} | 120 | V | 25°C |
| Gate-to-Source Voltage | V_{GS} | -10, +2 | | |
| Power Dissipation | P_{DISS} | 7 | W | |
| Storage Temperature | T_{STG} | -65, +150 | °C | |
| Operating Junction Temperature | T_J | 225 | | |
| Maximum Forward Gate Current | I_{GMAX} | 4.0 | mA | 25°C |
| Maximum Drain Current ¹ | I_{DMAX} | 1.5 | A | |
| Soldering Temperature ² | T_S | 245 | °C | |
| Screw Torque | τ | 40 | in-oz | |
| Thermal Resistance, Junction to Case ³ | $R_{\theta JC}$ | 8.0 | °C/W | 85°C |
| Case Operating Temperature ³ | T_C | -40, +150 | °C | |

Notes:

¹ Current limit for long term, reliable operation

² Refer to the Application Note on soldering

³ Measured for the CGH35015 at $P_{DISS} = 7$ W.

Electrical Characteristics ($T_C = 25^\circ\text{C}$)

| Characteristics | Symbol | Min. | Typ. | Max. | Units | Conditions |
|--|---------------|------|------|------|----------|--|
| DC Characteristics¹ | | | | | | |
| Gate Threshold Voltage | $V_{GS(th)}$ | -3.8 | -3.0 | -2.3 | V_{DC} | $V_{DS} = 10$ V, $I_D = 3.6$ mA |
| Gate Quiescent Voltage | $V_{GS(Q)}$ | – | -2.7 | – | | $V_{DS} = 28$ V, $I_D = 60$ mA |
| Saturated Drain Current | I_{DS} | 2.9 | 3.5 | – | A | $V_{DS} = 6.0$ V, $V_{GS} = 2.0$ V |
| Drain-Source Breakdown Voltage | $V_{(BR)DSS}$ | 84 | – | – | V_{DC} | $V_{GS} = -8$ V, $I_D = 3.6$ mA |
| RF Characteristics^{2,3} ($T_C = 25^\circ\text{C}$, $F_0 = 3.5$ GHz unless otherwise noted) | | | | | | |
| Small Signal Gain | G_{SS} | 10.5 | 12 | – | dB | $V_{DD} = 28$ V, $I_{DQ} = 100$ mA |
| Drain Efficiency ⁴ | η | 22 | 26 | – | % | $V_{DD} = 28$ V, $I_{DQ} = 100$ mA, $P_{AVE} = 2.0$ W |
| Back-Off Error Vector Magnitude | EVM | – | 2.5 | – | | $V_{DD} = 28$ V, $I_{DQ} = 100$ mA, $P_{AVE} = 18$ dBm |
| Error Vector Magnitude | | – | | – | | $V_{DD} = 28$ V, $I_{DQ} = 100$ mA, $P_{AVE} = 2.0$ W |
| Output Mismatch Stress | VSWR | – | – | 10:1 | Ψ | No damage at all phase angles, $V_{DD} = 28$ V, $I_{DQ} = 100$ mA, $P_{AVE} = 2.0$ W |
| Dynamic Characteristics | | | | | | |
| Input Capacitance | C_{GS} | – | 4.5 | – | pF | $V_{DS} = 28$ V, $V_{GS} = -8$ V, $f = 1$ MHz |
| Output Capacitance | C_{DS} | – | 1.3 | – | | |
| Feedback Capacitance | C_{GD} | – | 0.2 | – | | |

Notes:

¹ Measured on wafer prior to packaging

² Measured in the CGH35015F-AMP test fixture

³ Under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, 5ms Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3, PAR = 9.8 dB @ 0.01% Probability on CCDF

⁴ Drain Efficiency = P_{OUT} / P_{DC}

Typical WiMAX Performance




Figure 1. Small Signal S-Parameters vs Frequency measured in the CGH35015F-AMP
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$




Figure 2. Typical EVM and Efficiency versus Frequency measured in the CGH35015F-AMP
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$, 802.16-2004 OFDM, PAR = 9.8 dB

Note:
¹ 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3

Typical WiMAX Performance




Figure 3. Drain Efficiency and Gain vs Output Power measured in the CGH35015F-AMP
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$, 802.16-2004 OFDM, PAR = 9.8 dB




Figure 4. Typical EVM and Efficiency vs Output Power measured in the CGH35015F-AMP
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$, 802.16-2004 OFDM, PAR = 9.8 dB

Note:
¹ Under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3

Typical Performance




Figure 5. Simulated Maximum Available Gain and K Factor of the CGH35015
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$

Typical Noise Performance





Figure 6. Simulated Minimum Noise Figure and Noise Resistance vs Frequency of the CGH35015
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 100\text{ mA}$

Source and Load Impedances



| Frequency (MHz) | Z Source | Z Load |
|-----------------|--------------|-------------|
| 3300 | 13.0 - j5.6 | 13.2 - j2.8 |
| 3400 | 17.2 - j6.0 | 13.2 - j2.8 |
| 3500 | 20.8 - j9.9 | 13.1 - j2.9 |
| 3600 | 20.1 - j15.8 | 13.1 - j3.3 |
| 3700 | 15.7 - j19.0 | 12.3 - j3.8 |

Notes:

¹ $V_{DD} = 28V$, $I_{DQ} = 115\text{ mA}$ in the 440166 package

² Impedances are extracted from the CGH35015F-AMP demonstration amplifier and are not source and load pull data derived from the transistor


Electrostatic Discharge (ESD) Classifications

| Parameter | Symbol | Class | Classification Level | Test Methodology |
|---------------------|--------|-------|--------------------------------|---------------------|
| Human Body Model | HBM | TBD | ANSI/ESDA/JEDEC JS-001 Table 3 | JEDEC JESD22 A114-D |
| Charge Device Model | CDM | TBD | ANSI/ESDA/JEDEC JS-002 Table 3 | JEDEC JESD22 C101-C |


CGH35015F-AMP Demonstration Amplifier Circuit Bill of Materials

| Designator | Description | Qty |
|------------|--|-----|
| C1, C2 | CAP, 0.8pF, +/-0.1pF, 0603, ATC 600S | 2 |
| C10, C11 | CAP, 2.4pF, +/-0.1pF, 0603, ATC 600S | 2 |
| C4, C12 | CAP, 10.0pF, +/-5%, 0603, ATC 600S | 1 |
| C5, C13 | CAP, 39pF ±5%, 0603, ATC 600S | 2 |
| C14 | CAP, 100pF ±5%, 0603, ATC 600S | 1 |
| C6 | CAP, 470pF ±10%, 100V, 0603 | 1 |
| C7, C15 | CAP, 33000pF, 100V, 0805, X7R | 2 |
| C8 | CAP, 10μF, 16V, SMT, TANTALUM (240096) | 1 |
| C16 | CAP, 1.0μF ±10%, 100V, 1210, X7R | 1 |
| C17 | CAP, 33μF, 100V, ELECT, FK, SMD | 1 |
| R3 | RES, 1/16W, 0603, 22 Ohms ≤5% | 1 |
| R4 | RES, 1/16W, 0603, 100 Ohms ≤5% | 1 |
| J1 | 5-PIN, MOLEX, MALE, CONNECTOR | 1 |
| J2 | 2-PIN, MOLEX, MALE, CONNECTOR | 1 |
| J3, J4 | SMA, FEMALE, CONNECTOR | 2 |
| - | PCB, RO4350B, Er = 3.48, h = 20 mil | 1 |
| - | CGH35015F or CGH35015P | 1 |


CGH35015F-AMP Demonstration Amplifier Circuit



CGH35015-AMP Demonstration Amplifier Circuit Schematic



CGH35015-AMP Demonstration Amplifier Circuit Outline




Typical Package S-Parameters for CGH35015
(Small Signal, $V_{DS} = 28$ V, $I_{DQ} = 100$ mA, angle in degrees)

| Frequency | Mag S11 | Ang S11 | Mag S21 | Ang S21 | Mag S12 | Ang S12 | Mag S22 | Ang S22 |
|-----------|---------|---------|---------|---------|---------|---------|---------|---------|
| 500 MHz | 0.909 | -124.41 | 17.41 | 107.81 | 0.026 | 21.06 | 0.335 | -93.73 |
| 600 MHz | 0.902 | -134.04 | 15.04 | 101.48 | 0.027 | 15.39 | 0.322 | -101.61 |
| 700 MHz | 0.898 | -141.62 | 13.18 | 96.16 | 0.028 | 10.74 | 0.315 | -107.78 |
| 800 MHz | 0.894 | -147.78 | 11.71 | 91.54 | 0.028 | 6.79 | 0.312 | -112.73 |
| 900 MHz | 0.892 | -152.91 | 10.51 | 87.43 | 0.028 | 3.35 | 0.312 | -116.77 |
| 1.0 GHz | 0.890 | -157.30 | 9.53 | 83.68 | 0.028 | 0.28 | 0.314 | -120.15 |
| 1.1 GHz | 0.889 | -161.12 | 8.71 | 80.20 | 0.028 | -2.51 | 0.318 | -123.04 |
| 1.2 GHz | 0.889 | -164.51 | 8.01 | 76.95 | 0.028 | -5.07 | 0.322 | -125.57 |
| 1.3 GHz | 0.888 | -167.56 | 7.41 | 73.86 | 0.028 | -7.45 | 0.328 | -127.82 |
| 1.4 GHz | 0.888 | -170.34 | 6.89 | 70.91 | 0.028 | -9.69 | 0.335 | -129.87 |
| 1.5 GHz | 0.888 | -172.91 | 6.44 | 68.07 | 0.028 | -11.81 | 0.342 | -131.77 |
| 1.6 GHz | 0.888 | -175.30 | 6.04 | 65.32 | 0.028 | -13.82 | 0.349 | -133.56 |
| 1.7 GHz | 0.888 | -177.55 | 5.69 | 62.65 | 0.027 | -15.74 | 0.357 | -135.25 |
| 1.8 GHz | 0.888 | -179.68 | 5.37 | 60.05 | 0.027 | -17.58 | 0.364 | -136.89 |
| 1.9 GHz | 0.888 | 178.29 | 5.09 | 57.50 | 0.027 | -19.34 | 0.373 | -138.48 |
| 2.0 GHz | 0.888 | 176.34 | 4.83 | 55.01 | 0.027 | -21.04 | 0.381 | -140.03 |
| 2.1 GHz | 0.889 | 174.45 | 4.60 | 52.56 | 0.026 | -22.69 | 0.389 | -141.55 |
| 2.2 GHz | 0.889 | 172.63 | 4.39 | 50.14 | 0.026 | -24.27 | 0.397 | -143.06 |
| 2.3 GHz | 0.889 | 170.84 | 4.20 | 47.76 | 0.026 | -25.80 | 0.405 | -144.56 |
| 2.4 GHz | 0.889 | 169.10 | 4.02 | 45.41 | 0.025 | -27.28 | 0.413 | -146.04 |
| 2.5 GHz | 0.890 | 167.39 | 3.86 | 43.09 | 0.025 | -28.70 | 0.421 | -147.52 |
| 2.6 GHz | 0.890 | 165.71 | 3.71 | 40.79 | 0.025 | -30.08 | 0.429 | -149.00 |
| 2.7 GHz | 0.891 | 164.04 | 3.57 | 38.51 | 0.024 | -31.41 | 0.437 | -150.48 |
| 2.8 GHz | 0.891 | 162.39 | 3.44 | 36.26 | 0.024 | -32.69 | 0.445 | -151.95 |
| 2.9 GHz | 0.891 | 160.76 | 3.32 | 34.01 | 0.024 | -33.92 | 0.452 | -153.43 |
| 3.0 GHz | 0.892 | 159.13 | 3.21 | 31.79 | 0.023 | -35.10 | 0.459 | -154.92 |
| 3.2 GHz | 0.892 | 155.89 | 3.00 | 27.38 | 0.023 | -37.31 | 0.473 | -157.90 |
| 3.4 GHz | 0.893 | 152.65 | 2.83 | 23.00 | 0.022 | -39.32 | 0.486 | -160.90 |
| 3.6 GHz | 0.893 | 149.39 | 2.67 | 18.66 | 0.021 | -41.09 | 0.499 | -163.93 |
| 3.8 GHz | 0.894 | 146.09 | 2.54 | 14.34 | 0.020 | -42.63 | 0.510 | -166.99 |
| 4.0 GHz | 0.894 | 142.74 | 2.41 | 10.02 | 0.020 | -43.90 | 0.521 | -170.10 |
| 4.2 GHz | 0.895 | 139.33 | 2.31 | 5.70 | 0.019 | -44.88 | 0.530 | -173.24 |
| 4.4 GHz | 0.895 | 135.84 | 2.21 | 1.37 | 0.018 | -45.53 | 0.539 | -176.45 |
| 4.6 GHz | 0.895 | 132.26 | 2.12 | -2.98 | 0.018 | -45.84 | 0.547 | -179.71 |
| 4.8 GHz | 0.895 | 128.59 | 2.04 | -7.36 | 0.017 | -45.78 | 0.554 | 176.97 |
| 5.0 GHz | 0.895 | 124.80 | 1.97 | -11.79 | 0.016 | -45.32 | 0.561 | 173.56 |
| 5.2 GHz | 0.895 | 120.90 | 1.91 | -16.27 | 0.016 | -44.47 | 0.566 | 170.07 |
| 5.4 GHz | 0.895 | 116.87 | 1.85 | -20.81 | 0.016 | -43.25 | 0.571 | 166.48 |
| 5.6 GHz | 0.895 | 112.70 | 1.80 | -25.41 | 0.015 | -41.72 | 0.575 | 162.78 |
| 5.8 GHz | 0.895 | 108.38 | 1.75 | -30.10 | 0.015 | -39.97 | 0.579 | 158.96 |
| 6.0 GHz | 0.895 | 103.92 | 1.70 | -34.88 | 0.016 | -38.13 | 0.581 | 155.00 |

To download the s-parameters in s2p format, go to the CGH35015 Product Page.

Product Dimensions CGH35015F (Package Type — 440166)




- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. ADHESIVE FROM LID MAY EXTEND A MAXIMUM OF 0.020" BEYOND EDGE OF LID.
 4. LID MAY BE MISALIGNED TO THE BODY OF THE PACKAGE BY A MAXIMUM OF 0.008" IN ANY DIRECTION.
 5. ALL PLATED SURFACES ARE NI/AU

| DIM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.155 | 0.165 | 3.94 | 4.19 |
| B | 0.004 | 0.006 | 0.10 | 0.15 |
| C | 0.115 | 0.135 | 2.92 | 3.43 |
| D | 0.057 | 0.067 | 1.45 | 1.70 |
| E | 0.195 | 0.205 | 4.95 | 5.21 |
| F | 0.045 | 0.055 | 1.14 | 1.40 |
| G | 0.545 | 0.555 | 13.84 | 14.09 |
| H | 0.280 | 0.360 | 7.11 | 9.14 |
| J | Ø .100 | | 2.54 | |
| K | 0.375 | | 9.53 | |

- PIN 1. GATE
 PIN 2. DRAIN
 PIN 3. SOURCE

Product Dimensions CGH35015P (Package Type — 440196)






- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. ADHESIVE FROM LID MAY EXTEND A MAXIMUM OF 0.020" BEYOND EDGE OF LID.
 4. LID MAY BE MISALIGNED TO THE BODY OF THE PACKAGE BY A MAXIMUM OF 0.008" IN ANY DIRECTION.
 5. ALL PLATED SURFACES ARE NI/AU

| DIM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.155 | 0.165 | 3.94 | 4.19 |
| B | 0.003 | 0.006 | 0.10 | 0.15 |
| C | 0.115 | 0.135 | 2.92 | 3.17 |
| D | 0.057 | 0.067 | 1.45 | 1.70 |
| E | 0.195 | 0.205 | 4.95 | 5.21 |
| F | 0.045 | 0.055 | 1.14 | 1.40 |
| G | 0.195 | 0.205 | 4.95 | 5.21 |
| H | 0.280 | 0.360 | 7.11 | 9.14 |

- PIN 1. GATE
 PIN 2. DRAIN
 PIN 3. SOURCE

Product Ordering Information

| Order Number | Description | Unit of Measure | Image |
|--------------|------------------------------------|-----------------|--|
| CGH35015F | GaN HEMT | Each |  |
| CGH35015P | GaN HEMT | Each |  |
| CGH35015-AMP | Test board with GaN HEMT installed | Each |  |

Notes & Disclaimer

MACOM Technology Solutions Inc. ("MACOM"). All rights reserved.

These materials are provided in connection with MACOM's products as a service to its customers and may be used for informational purposes only. Except as provided in its Terms and Conditions of Sale or any separate agreement, MACOM assumes no liability or responsibility whatsoever, including for (i) errors or omissions in these materials; (ii) failure to update these materials; or (iii) conflicts or incompatibilities arising from future changes to specifications and product descriptions, which MACOM may make at any time, without notice. These materials grant no license, express or implied, to any intellectual property rights.

THESE MATERIALS ARE PROVIDED "AS IS" WITH NO WARRANTY OR LIABILITY, EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHT, ACCURACY OR COMPLETENESS, OR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES WHICH MAY RESULT FROM USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.