

### Features

- High Power Handling
- Low Loss / Low Distortion
- Leadless Low Inductance MELF Package
- Surface Mountable
- RoHS Compliant


### Description

The chip used in the MA4PH611 is manufactured using a unique, CERMACHIP, passivation process which provides for a hard glass encapsulation that protects and hermetically seals the active area of the chip. This packaged, CERMACHIP, PIN diode is ideally suited for use in applications where high RF and DC voltages are present.


The chip is enclosed in a rugged, ceramic, Metal Electrode Leadless Faced (MELF), surface mount package that is full face bonded to refractory metal plugs on both the anode and cathode. The result is a low loss PIN diode with low thermal resistance due to its symmetrical thermal paths. MELF PIN diodes are designed specifically for high volume tape and reel assembly. Their user friendly design provides for extremely easy, automatic, pick and place, indexing and assembly. All solderable surfaces are tin plated and are compatible with all industry standard reflow and vapor phase solder processes.

The MA4PH611 is well suited for use in low loss, low distortion, UHF and VHF high power switching circuits.

Dot Denotes Cathode




Full Face Chip Bond



Passivated PIN Chip


Diode Cross Section

### Package Dimensions (ODS-1091)



Dim.	Inches		mm	
	Min.	Max.	Man.	Max.
A	0.138	0.155	3.51	3.94
B	0.180	0.200	4.57	5.08
C	0.008	0.030	0.203	0.762

### Circuit Pad Layout



Dim.	Inches	mm
A	0.150	3.81
B	0.050	1.27
C	0.100	2.54

### Ordering Information<sup>1</sup>

Part Number	Package
MA4PH611	Package style 1091T 500 piece reel

1. Reference Application Note M513 for reel size information.

### Electrical Specifications: $T_A = +25^\circ\text{C}$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Forward Voltage	$I_F = 250 \text{ mA}$	V	—	—	1.1
Reverse Leakage	$V_R = 1000 \text{ V}$	nA	—	—	1000
Total Capacitance	$V_R = 50 \text{ V}, 1 \text{ MHz}$	pF	—	0.95	1.1
Series Resistance	$I_F = 100 \text{ mA}, 100 \text{ MHz}$	W	—	0.35	0.45
Parallel Resistance	$0 \text{ V}, 100 \text{ MHz}$	kW	25	—	—
Lifetime	$I_F = 10 \text{ mA}, I_R = 6 \text{ mA}$	$\mu\text{s}$	5	—	—

### Maximum Thermal Characteristics

Parameter	Test Conditions	Units	Max.
Thermal Resistance	Infinite Heatsink In Air	$^\circ\text{C/W}$	15
			42
Power Dissipation <sup>2</sup>	Infinite Heatsink In Air	W	10.0
			3.5

2. De-rate linearly by  $-77 \text{ mw}/^\circ\text{C}$  to  $0 \text{ W}$  @  $+175^\circ\text{C}$  junction temperature.

### Absolute Maximum Ratings<sup>3,4</sup>


Parameter	Absolute Maximum
DC Reverse Voltage	1000 V
Operating Chip Junction Temperature	$-55^\circ\text{C}$ to $+175^\circ\text{C}$
Storage Temperature	$-55^\circ\text{C}$ to $+200^\circ\text{C}$
Installation Temperature	$+280^\circ\text{C}$ for 10 Seconds

3. Exceeding any one or combination of these limits may cause permanent damage to this device.


4. MACOM does not recommend sustained operation near these survivability limits.

### Typical Performance Curves


**Total Capacitance vs. Voltage @ 100 MHz**




**Series Resistance vs. Current @ 100 MHz**



**Parallel Resistance vs. Voltage @ 500 MHz**



**Parallel Resistance vs. Frequency @ 0 V**



### Assembly Recommendations

- Devices may be soldered using standard Sn63/Pb37 or any RoHS compliant solder. Leads are bright tin plated to a minimum thickness of 50µm to ensure an optimum connection.
- For recommended Sn/Pb and RoHS soldering time/temperature profiles. See Application Note M538 on the MACOM website.

### Handling Procedures

The following precautions should be observed to avoid damaging these devices.

### Cleanliness and Storage

MELF devices should be handled and stored in a clean environment. The metalized ends of the device are tin plated for greater solderability and any continuous exposure to high humidity (>80%) for extended periods of time may cause the surface to oxidize. Caution should be taken when storing devices for extended intervals.

### ESD

These devices are susceptible to ESD and are rated Class 1C.

### General Handling

Device can be handled with tweezers or vacuum pickups and are suitable for use with automatic pick-and-place equipment.

### RoHS

The MA4PH611 is fully RoHS compliant meaning it contains less than the maximum allowable concentration of 0.1%, by weight, in homogenous materials for lead, hex chrome, mercury, PBB, PBDE, and 0.01% for cadmium.

### Mounting Techniques

#### Solder Attach

Typical wave soldering or reflow techniques may be used to mount MELF packages to circuit boards. Alloys such as Sn63/Pb37 or any RoHS compliant solder may be used. For more information visit the MACOM website and refer to application note M538.

To view the datasheets of other MELF and packaged PIN diodes on the MACOM website please see PACKAGED\_PIN\_DIODES and/or MA4P MELF & HIPAX SERIES

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.