

## 16:1 Flux Coupled Transformer 5 - 90 MHz

Rev. V2

### Features



- 16:1 Flux Coupled
- Surface Mount Package
- 260°C Reflow Compatible
- RoHS v Compliant Version of MABACT0046

### Description

The MABA-008282-CFGA40 is a 16:1 flux coupled transformer in a surface mount package.

Ideally suited for high volume CATV/Broadband applications. Suitable for use in both 50  $\Omega$  & 75  $\Omega$  systems.

### Schematic



### Pin Configuration

Pin #	Function
1	Secondary Dot (output 2)
2	Centre Tap
3	Secondary (output 1)
4	Primary (ground)
5	Primary Dot

### Electrical Specifications: $T_A = 25^\circ\text{C}$ , $Z_0 = 75 \Omega$ , $P_{IN} = 0 \text{ dBm}$

Parameter	Frequency	Units	Min.	Typ.	Max.
Insertion Loss	5 - 15 MHz	dB	—	1.3	1.8
	15 - 63 MHz			1.1	1.7
	63 - 90 MHz			1.9	2.5
Amplitude Balance	5 - 90 MHz	dB	—	$\pm 0.03$	$\pm 0.15$
Phase Balance	5 - 90 MHz	$^\circ$	—	$\pm 0.1$	$\pm 1.0$
Input Return Loss	5 - 63 MHz	dB	7	13	—
	63 - 90 MHz		4	6	

### Ordering Information

Part #	Description
MABA-008282-CFGA40	2000 piece reel
MABA-008282-CFGATB	customer test board


Reference Application Note **M513** for reel size information.

### Absolute Maximum Ratings


Parameter	Absolute Maximum
RF Power	250 mW
DC current	30 mA
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C

Typical Performance Curves:  $T_A = 25^\circ\text{C}$ ,  $Z_0 = 75 \Omega$ ,  $P_{IN} = 0 \text{ dBm}$


**Insertion Loss 1 (Pin5—Pin3)**




**Insertion Loss 2 (Pin5—Pin1)**




**Amplitude Balance**




**Phase Balance**



**Return Loss: Input**



## Outline Drawing (SM-164)



Dimensions in inches [mm] Tolerance: .xx ± .02, .xxx ± .010, unless otherwise stated

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.