

Transformer, 1:20 8.2 MHz

Rev. V3

Features


- Surface Mount
- 260°C reflow compatible
- · RoHS compliant, lead-free
- Available on Tape and Reel

Description


MABA-011006 is a 1:20 flux coupled transformer in a low cost package.



Application Circuit:



Case style:



All dimensions are in mm

Tolerance: ±0.2mm unless otherwise noted

Electrical Specifications: $Z_0 = 50\Omega$, $T_A = 25$ °C, $P_{in} = 0$ dBm

| Frequency | S11 (dB)(max) | S11 (dB)(min) |
|-----------|---------------|---------------|
| 8.2 MHz | -0.79 | -0.96 |

MABA-011006



Transformer, 1:20 8.2 MHz

Rev. V3

Tape & Reel Information

| Parameter | Units | Value | | |
|--|-------|-------|--|--|
| Qty per reel | - | 900 | | |
| Reel Size | mm | 330 | | |
| Tape Width | mm | 16.00 | | |
| Pitch | mm | 12.00 | | |
| Ao | mm | 6.80 | | |
| Во | mm | 7.60 | | |
| Ko | mm | 5.30 | | |
| Orientation | - | F15 | | |
| Reference Application Note ANI-019 for orientation | | | | |

Ordering Information

| Part Number | Description | | |
|----------------|---------------------|--|--|
| MABA-011006 | Tape & Reel | | |
| MABA-011006-TB | Customer test board | | |

Recommended Maximum Ratings

| Parameter | Units | Min | Max |
|-----------------------------|-------|-----|-----|
| Input Power | mW | | 250 |
| DC Current | mA | | 30 |
| Operating Temperature Range | °C | -40 | +85 |

Temperature data available on request

MABA-011006



Transformer, 1:20 8.2 MHz

Rev. V3

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.