

Diode Limiter

2 - 40 GHz



MADL-011116

Rev. V1

Features

- Peak Power Handling: 10 W
- CW Power Handling: 3.5 W
- Low Insertion Loss: 1.4 dB @ 40 GHz
- Flat Leakage Power: 17 dBm @ 40 GHz
- 4 mm Air cavity SMT package
- Passive Device
- RoHS* Compliant

Applications

- Receiver Protection
- Radar Systems
- Radio Frequency Front-End Modules

Description

MADL-011116 is a fully integrated diode limiter. It is a passive device, DC decoupled at both input and output RF ports.

The limiter can handle 10 W peak power at 40 GHz with a low flat leakage of 17 dBm.


MADL-011116 is ideally suited for high frequency, high peak power receiver protection with the convenience of a highly integrated surface mount solution.

Ordering Information¹

Part Number	Package
MADL-011116-TR0250	250 pc. tape & reel
MADL-011116-SMB	Sample Board

1. Reference Application Note M513 for reel size information.

Functional Schematic



Pin Configuration²

Pin #	Function
1	RF Input
2, 4	NC
3	RF Output
5 (Paddle)	Ground ³

2. MACOM recommends connecting unused package pins to ground.
3. The exposed pad centered on the package bottom must be connected to RF, DC and thermal ground.

* Restrictions on Hazardous Substances, compliant to current RoHS EU directive.

Electrical Specifications: $T_A = +25^\circ\text{C}$, $Z_0 = 50 \Omega$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Insertion Loss	2 GHz 18 GHz 40 GHz	dB	—	0.8 1.2 1.4	—
Input & Output Return Loss	—	dB	—	15	—
CW Power Handling	—	dBm	—	35.5	—
CW Flat Leakage	2 GHz 18 GHz 40 GHz	dBm	—	17 21 17	—
CW P1dB	—	dBm	—	22	—
Pulsed Peak Power Handling	1 μs PW, 1% Duty Cycle	dBm	—	40	—
Spike Leakage Power	1 μs PW, 1% DC, 33 dBm Input 2 GHz 18 GHz 40 GHz	dBm	—	16 12 7	—
Spike Leakage Energy	1 μs PW, 1% DC, 33 dBm Input 18 GHz 26 GHz 40 GHz	ergs	—	8.8e-3 2.4e-3 1.7e-3	—
1 dB Recovery Time	1 μs PW, 1% DC, 33 dBm Input	ns	—	25	—
3 dB Recovery Time	1 μs PW, 1% DC, 33 dBm Input	ns	—	20	—

Absolute Maximum Ratings^{4,5}

Parameter	Absolute Maximum
CW Incident Power	36 dBm @ +85°C
Peak Incident Power	40.5 dBm @ +85°C
Junction Temperature ⁶	+150°C
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +150°C

4. Exceeding any one or combination of these limits may cause permanent damage to this device.
5. MACOM does not recommend sustained operation near these survivability limits.
6. Operating at nominal conditions with $T_J \leq +150^\circ\text{C}$ will ensure $\text{MTTF} > 1 \times 10^6$ hours.

Handling Procedures

Please observe the following precautions to avoid damage:

Static Sensitivity

These electronic devices are sensitive to electrostatic discharge (ESD) and can be damaged by static electricity. Proper ESD control techniques should be used when handling these devices.

Diode Limiter 2 - 40 GHz




MADL-011116


Rev. V1

Typical Small-Signal Performance: Package On-Board: $T_A = -40^\circ\text{C}, 25^\circ\text{C}, 85^\circ\text{C}, Z_0 = 50 \Omega$


Insertion Loss



Input Return Loss




Output Return Loss




**Typical RF Power Performance: Package On-Board: $Z_0 = 50 \Omega$, $T_A = 25^\circ\text{C}$,
1 μs Pulse Width, 1% Duty Cycle**


Pulsed Flat Leakage Power over Frequency




1dB and 3dB Recovery time at 33 dBm Input



Pulsed Spike Peak Power over Input Power



Pulsed Spike Energy Power over Input Power



Diode Limiter 2 - 40 GHz




MADL-011116


Rev. V1

Typical RF Power Performance: Package On-Board: $T_A = 25^\circ\text{C}$, $Z_0 = 50 \Omega$


CW Flat leakage Power over Frequency



CW Gain Compression over Frequency



CW 1dB Compression Point




Diode Limiter 2 - 40 GHz



MADL-011116

Rev. V1

Lead-Free 4 mm 4-Lead PQFN[†]



[†] Reference Application Note S2083 for lead-free solder reflow recommendations.
 Meets JEDEC moisture sensitivity level MSL 3 requirements.
 Plating is gold. This device is non-hermetic with an open vent hole. MACOM does not recommend performing any aqueous cleaning process post-assembly unless the vent hole has been filled post-reflow.
 Limiter is NOT Bi-Directional, pin 1 is RF Input.

MACOM Technology Solutions Inc. ("MACOM"). All rights reserved.

These materials are provided in connection with MACOM's products as a service to its customers and may be used for informational purposes only. Except as provided in its Terms and Conditions of Sale or any separate agreement, MACOM assumes no liability or responsibility whatsoever, including for (i) errors or omissions in these materials; (ii) failure to update these materials; or (iii) conflicts or incompatibilities arising from future changes to specifications and product descriptions, which MACOM may make at any time, without notice. These materials grant no license, express or implied, to any intellectual property rights.

THESE MATERIALS ARE PROVIDED "AS IS" WITH NO WARRANTY OR LIABILITY, EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHT, ACCURACY OR COMPLETENESS, OR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES WHICH MAY RESULT FROM USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.