Microstrip PIN Diode

Features

- Supports up to 40 Watts Power
- Low Insertion Loss 0.38 dB typical at 10 GHz
- High Isolation 55 dB typical at 40 GHz
- RoHS* Compliant

Description

A broadband medium power PIN diode is designed as a 50 Ω microstrip when biased at zero or a negative voltage. The device has extremely high isolation from 50 MHz to 40 GHz and can achieve switching speeds <250 ns.

Electrical Specifications: T_c = +25°C

Parameter **Test Conditions** Units Min. Typ. Max. Breakdown Voltage V 200 $I_{R} = 10 \ \mu A$ I_F = 100 mA. 500 MHz Series Resistance Ω 0.6 Minority Carrier Lifetime $I_F = 10 \text{ mA}, I_R = 6 \text{ mA}, 10\% / 90\%$ 4000 ns V_{R} = -40 V, 10 GHz 0.38 0.65 Insertion Loss dB V_{R} = -40 V, <40 GHz 1.35 10 GHz 17 21 Input Return Loss dB <40 GHz 12 $I_{\rm F} = 100 \text{ V}, 10 \text{ GHz},$ 50 58 Isolation dB I_F = 100 V, <40 GHz 50

Absolute Maximum Ratings

Parameter	Absolute Maximum
Reverse Voltage	200 V
Forward Current	100 mA
Thermal Resistance	65°C/W
Junction Temperature	+150°C
Storage Temperature	-65°C to +125°C
Assembly Temperature	+260°C, per JEDEC STD-J-20C

Ordering Information


Part Number	Package
MMSPN050-C54	bulk

* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.

For further information and support please visit: <u>https://www.macom.com/support</u>

1






Rev. V1


Microstrip PIN Diode

Typical Performance Curves: T_A = +25°C, Z_O = 50 Ω , -10 dBm Small Signal




Isolation 0 -10 10 mA 20 mA ----- 40 mA -20 Isolation (dB) -30 -40 -50 -60 -70 0 10 20 30 40 Frequency (GHz)

Input Return Loss



Resistance vs. Current @ 500 MHz



2

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.



Microstrip PIN Diode


Rev. V1


Recommended Assembly for Best Thermals



For best isolation and to minimize coupling between the input and output, keep the bond wire height to a minimum.


Outline Drawing (C54)





Dimensions in mils [mm]

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit www.macom.com for additional data sheets and product information.



3

Electrical Schematic



Microstrip PIN Diode



Rev. V1

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

⁴

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.